

# NEW

# S500

## TRACKED CARRIER

### Traction for Any Terrain, Payload for Serious Work.

**S500**  
Tracked Carrier

**11,000 lb Payload**

**128hp Kubota Diesel**



### Heated & Air Conditioned Cab

Helping crews stay productive in hot, cold, wet, dusty, and windy conditions.



### Built for Every Jobsite

Utility right-of-way to quarry work, logging roads, and major site prep.



### HD Rubber Track Undercarriage

Confident grip in mud, rock, and uneven ground, with a stable footprint that helps you haul heavy loads where others struggle.

**GANYCOM**

# Key Features



Intuitive joystick controls for precise, comfortable maneuverability.



Around View monitor and camera system with cameras on rear and sides for 360 degree viewing.



11,000 lb payload and large bed capacity for efficient material transport.



# Specifications

S500V					
Dimensions	Machine Weight	14,440 lb (6,550 kg)	Drivetrain	Transmission	HST (2-stage selection)
	Max Payload	11,023 lb (5,000 kg)		Travel Speed (High)	0-8.7 mph (0-14 km/h)
	Length	186 in (4,725 mm)		Travel Speed (Low)	0-6.2 mph (0-10 km/h)
	Width	88.6 in (2,250 mm)		Min. Turning Radius	~10.2 ft (3.1 m)
	Height	104.3 in (2,650 mm)		Gradeability	25° (empty)
	Ground Clearance	17.9 in (455 mm)		Steering System	2 pump - 2 motor
	Ground Contact Length	91.3 in (2,320 mm)		Brakes	Negative brake (hydraulic)
	Track Tread	65.0 in (1,650 mm)		Track Size	23.6 x 4.9 x 2.5 in (600 x 125 x 64 mm)
	Machine Floor Height	44.5 in (1,130 mm)		Dump System	Hydraulic dump (Straight Dump)
Engine	Engine Model	Kubota V3800	Bucket / Dumping	Dump Angle	60° (level ground)
	Engine Type	4-cycle, water-cooled, in-line 4-cyl diesel		Lift Time	~9.0 sec
	Displacement	230.0 cu in (3,769 cc)		Lower Time	~6.0 sec
	Rated Output	127.4 hp (95 kW) @ 2,400 rpm		Capacity (Struck)	63.9 cu ft (1.81 m³)
	Max Torque	324.5 lbf-ft (440 N-m) @ 1,800 rpm		Capacity (Heaped)	104.9 cu ft (2.97 m³)



**Canycom USA, Inc.**

888-450-0381

425-450-0381

info@canycomsales.com

www.canycomsales.com

